

S-WORKS EPIC HARDTAIL AXS

Euro 9.399,00



Grigio Tortora Lucido / Rosso Rocket / Cremisi

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	S-Works FACT 12m, XC Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing.
FORCELLA	RockShox SID Brain Ultimate, top-adjust Brain Fade, tapered carbon crown and steerer, 15x110mm Maxle® Stealth thru-axle, 42mm offset, 100mm of travel
ATTACCO	S-Works SL, alloy, titanium bolts, 6-degree rise
MANUBRIO	S-Works Carbon XC Mini Rise, 6-degree upsweep, 8-degree backsweep, 10mm rise, 760mm, 31.8mm
MANOPOLE	Specialized Trail Grips
FRENO ANT.	SRAM Level Ultimate, hydraulic disc
FRENO POST.	SRAM Level Ultimate, hydraulic disc
CAMBIO POST.	SRAM XX1 Eagle AXS
COMANDI	SRAM XX1 Eagle AXS, trigger, 12-speed
CASSETTA	SRAM XG-1299 Eagle, 10-50t
CATENA	SRAM XX1 (Rainbow)
GUARNITURA	QUARQ XX1 Eagle Power Meter, Boost™ 148, DUB, 170/175mm
INGRANAGGI	Steel, 30T
MOVIM. CENTR.	SRAM DUB, threaded BB
CERCHI	Roval Control SL, hookless carbon, 25mm internal width, tubeless-ready, hand-built
MOZZO ANT.	Roval Control SL, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
MOZZO POST.	Roval Control SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
RAGGI	DT Swiss Competition Race
PNEUMATICO ANT.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry S-Works Power, carbon fiber rails, carbon fiber base, 143mm
REGGISELLA	S-Works FACT carbon, 10mm setback, 30.9mm

S-WORKS EPIC HARDTAIL

AXS	S	M	L	XL
Stack (mm)	608	608	622	636
Reach (mm)	405	430	455	480
Lunghezza Tubo sterzo (mm)	95	95	110	125
Angolo sterzo (degrees)	68.5	68.5	68.5	68.5
Altezza Mov. Centr. (mm)	309	309	309	309
BB Drop (mm)	63	63	63	63
Trail (mm)	101	101	101	101
Lunghezza intera forcella (mm)	506	506	506	506
Offset forcella / Rake (mm)	42	42	42	42
Avancorsa (mm)	668	693	723	753
Lunghezza Batticateni (mm)	430	430	430	430
Interasse (mm)	1090	1115	1146	1176
Lunghezza Tubo Orizz. virtuale (mm)	579	604	633	662
Altezza standover (mm)	762	792	816	847
Lunghezza piantone (mm)	400	430	470	520
Angolo Sella (degrees)	74	74	74	74

ART. NR.	DESCRIZIONE	COLORE	MISURA
91320-0102	EPIC HT SW CARBON SRAM AXS 29	Grigio Tortora Lucido / Rosso / Rocket / Cremisi	S
91320-0103			M
91320-0104			L
91320-0105			XL

S-WORKS EPIC HARDTAIL ULTRALIGHT

Euro 8.299,00



Nero/ Oro

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	S-Works FACT 12m, XC Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing.
FORCELLA	FOX Factory Step-Cast 32, Fit4 damper, Kashima, Boost™, 44mm offset, 100mm of travel, Kabolt
ATTACCO	S-Works SL, alloy, titanium bolts, 6-degree rise
MANUBRIO	S-Works Carbon XC Mini Rise, 6-degree upsweep, 8-degree backsweep, 10mm rise, 760mm, 31.8mm
MANOPOLE	ODI Vapor F-1 Series, slip-on
FRENO ANT.	Magura MT8 SL, Hydraulic Disc
FRENO POST.	Magura MT8 SL, Hydraulic Disc
CAMBIO POST.	SRAM XX1 Eagle, 12-speed
COMANDI	SRAM XX1 Eagle, trigger, 12-speed
CASSETTA	SRAM XG-1299 Eagle, 10-50t
CATENA	SRAM XX1 Eagle, 12-speed
GUARNITURA	SRAM XX1 Eagle, 148 DUB, 170/175mm, 32T
INGRANAGGI	Alloy, 32T
MOVIM. CENTR.	SRAM DUB, threaded BB
CERCHI	Roval Control SL 29, SRAM XX1, 148mm spacing
MOZZO ANT.	Roval Control SL, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
MOZZO POST.	Roval Control SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
RAGGI	DT Swiss Competition Race
PNEUMATICO ANT.	S-Works Renegade, S-Works Casing, GRIPTON® compound, 120 tpi, 2Bliss Ready, 29x2.1"
PNEUMATICO POST.	S-Works Renegade, S-Works Casing, GRIPTON® compound, 120 TPI, 2Bliss Ready, 29x2.1"
SELLA	Body Geometry S-Works Power Arc, carbon fiber rails, carbon fiber base, 143mm
REGGISELLA	S-Works FACT carbon, 10mm setback, 30.9mm

S-WORKS EPIC HARDTAIL ULTRALIGHT

	S	M	L	XL
Stack (mm)	608	608	622	636
Reach (mm)	405	430	455	480
Lunghezza Tubo sterzo (mm)	95	95	110	125
Angolo sterzo (degrees)	68.5	68.5	68.5	68.5
Altezza Mov. Centr. (mm)	309	309	309	309
BB Drop (mm)	63	63	63	63
Trail (mm)	101	101	101	101
Lunghezza intera forcella (mm)	506	506	506	506
Offset forcella / Rake (mm)	42	42	42	42
Avancorsa (mm)	668	693	723	753
Lunghezza Batticateni (mm)	430	430	430	430
Interasse (mm)	1090	1115	1146	1176
Lunghezza Tubo Orizz. virtuale (mm)	579	604	633	662
Altezza standover (mm)	762	792	816	847
Lunghezza piantone (mm)	400	430	470	520
Angolo Sella (degrees)	74	74	74	74

ART. NR.	DESCRIZIONE	COLORE	MISURA
91320-0302	EPIC HT SW CARBON ULTRALIGHT 29	Nero / Oro	S
91320-0303			M
91320-0304			L
91320-0305			XL

TELAIO S-WORKS EPIC HARDTAIL

Euro 2.999,00



Nero

SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le
caratteristiche senza preavviso.

TELAIO

S-Works FACT 12m, XC Geometry, Rider-First Engineered™,
threaded BB, 12x148mm rear spacing, internal cable routing.

TELAIO S-WORKS EPIC HARDTAIL

	S	M	L	XL
Stack (mm)	608	608	622	636
Reach (mm)	405	430	455	480
Lunghezza Tubo sterzo (mm)	95	95	110	125
Angolo sterzo (degrees)	68.5	68.5	68.5	68.5
Altezza Mov. Centr. (mm)	309	309	309	309
BB Drop (mm)	63	63	63	63
Trail (mm)	101	101	101	101
Lunghezza intera forcella (mm)	506	506	506	506
Offset forcella / Rake (mm)	42	42	42	42
Avancorsa (mm)	668	693	723	753
Lunghezza Batticateni (mm)	430	430	430	430
Interasse (mm)	1090	1115	1146	1176
Lunghezza Tubo Orizz. virtuale (mm)	579	604	633	662
Altezza standover (mm)	762	792	816	847
Lunghezza piantone (mm)	400	430	470	520
Angolo Sella (degrees)	74	74	74	74

ART. NR.	DESCRIZIONE	COLORE	MISURA
71320-0402	EPIC HT SW CARBON 29 TELAIO	Nero	S
71320-0403			M
71320-0404			L
71320-0405			XL

EPIC HARDTAIL PRO

Euro 5.499,00



Nero / Petrolio Cangiate

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	Specialized FACT 11m, XC Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing
FORCELLA	RockShox SID Brain 29, Solo Air, Position Sensitive, top-adjust Brain Fade, 15x110mm Maxle® Stealth thru-axle, 42mm offset, 100mm of travel
ATTACCO	Specialized XC, 3D-forged alloy, 4-bolt, 6-degree rise
MANUBRIO	S-Works Carbon XC Mini Rise, 6-degree upsweep, 8-degree backsweep, 10mm rise, 760mm, 31.8mm
MANOPOLE	Specialized Trail Grips
FRENO ANT.	SRAM Level TLM, hydraulic disc
FRENO POST.	SRAM Level TLM, hydraulic disc
CAMBIO POST.	SRAM X01 Eagle, 12-speed
COMANDI	SRAM X01 Eagle, trigger, 12-speed
CASSETTA	SRAM XG-1295 Eagle, 12-speed, 10-50t
CATENA	SRAM GX Eagle, 12-speed
GUARNITURA	SRAM X1 carbon Eagle, Boost™ 148, DUB, 170/175mm, 32T
INGRANAGGI	Alloy, 32T
MOVIM. CENTR.	SRAM DUB, threaded BB
CERCHI	Roval Control Carbon, 25mm internal width, tubeless-ready
MOZZO ANT.	Specialized, sealed cartridge bearings, 15x110mm spacing, 28h
MOZZO POST.	DT Swiss 350, Star Ratchet, 36t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry Power, Hollow Titanium rails, 143mm
REGGISELLA	Carbon, single-bolt, 30.9mm

EPIC HARDTAIL PRO	S	M	L	XL
Stack (mm)	608	608	622	636
Reach (mm)	405	430	455	480
Lunghezza Tubo sterzo (mm)	95	95	110	125
Angolo sterzo (degrees)	68.5	68.5	68.5	68.5
Altezza Mov. Centr. (mm)	309	309	309	309
BB Drop (mm)	63	63	63	63
Trail (mm)	101	101	101	101
Lunghezza intera forcella (mm)	506	506	506	506
Offset forcella / Rake (mm)	42	42	42	42
Avancorsa (mm)	668	693	723	753
Lunghezza Batticateni (mm)	430	430	430	430
Interasse (mm)	1090	1115	1146	1176
Lunghezza Tubo Orizz. virtuale (mm)	579	604	633	662
Altezza standover (mm)	762	792	816	847
Lunghezza piantone (mm)	400	430	470	520
Angolo Sella (degrees)	74	74	74	74

ART. NR.	DESCRIZIONE	COLORE	MISURA
91320-1102	EPIC HT PRO CARBON 29	Nero / Petrolio Cangiate	S
91320-1103			M
91320-1104			L
91320-1105			XL

EPIC HARDTAIL EXPERT

Euro 4.199,00



Carbonio Satinato / Nero

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	Specialized FACT 11m, XC Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing
FORCELLA	RockShox SID Brain 29, Solo Air, Position Sensitive, bottom-adjust Brain Fade, 15x110mm Maxle® Stealth thru-axle, 42mm offset, 100mm of travel (XS: 80mm travel)
ATTACCO	Specialized XC, 3D-forged alloy, 4-bolt, 6-degree rise
MANUBRIO	Specialized Alloy Minirise, 10mm rise, 750mm, 31.8mm clamp
MANOPOLE	Specialized Trail Grips
FRENO ANT.	SRAM Level TL, hydraulic disc
FRENO POST.	SRAM Level TL, hydraulic disc
CAMBIO POST.	SRAM GX Eagle, 12-speed
COMANDI	SRAM GX Eagle, trigger, 12-speed
CASSETTA	SRAM GX Eagle, 12-speed, 10-50t
CATENA	SRAM NX Eagle, 12-speed
GUARNITURA	Truvativ STYLO, DUB
INGRANAGGI	Alloy, 32T
MOVIM. CENTR.	SRAM DUB, threaded BB
CERCHI	Roval Control Carbon, 25mm internal width, tubeless-ready
MOZZO ANT.	Specialized, sealed cartridge bearings, 15x110mm spacing, 28h
MOZZO POST.	DT Swiss 370, SRAM XD 3-pawl driver body, 12mm thru-axle, 148mm spacing, 28h
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry Power Sport, hollow Cr-Mo rails
REGGISELLA	Specialized, alloy, single-bolt, 30.9mm

EPIC HARDTAIL EXPERT	XS	S	M	L	XL
Stack (mm)	594	608	608	622	636
Reach (mm)	385	405	430	455	480
Lunghezza Tubo sterzo (mm)	95	95	95	110	125
Angolo sterzo (degrees)	68.5	68.5	68.5	68.5	68.5
Altezza Mov. Centr. (mm)	309	309	309	309	309
BB Drop (mm)	63	63	63	63	63
Trail (mm)	101	101	101	101	101
Lunghezza intera forcella (mm)	486	506	506	506	506
Offset forcella / Rake (mm)	42	42	42	42	42
Avancorsa (mm)	641	668	693	723	753
Lunghezza Batticateni (mm)	430	430	430	430	430
Interasse (mm)	1062	1090	1115	1146	1176
Lunghezza Tubo Orizz. virtuale (mm)	555	579	604	633	662
Altezza standover (mm)	732	762	792	816	847
Lunghezza piantone (mm)	367	400	430	470	520
Angolo Sella (degrees)	74	74	74	74	74

ART. NR.	DESCRIZIONE	COLORE	MISURA
91320-3001	EPIC HT EXPERT CARBON 29	Carbonio Satinato / Nero	XS
91320-3002			S
91320-3003			M
91320-3004			L
91320-3005			XL

EPIC HARDTAIL COMP

Euro 2.699,00



Carbonio Satinato / Fluo



Grigio Tortora Lucido / Perlato Blu / Blu Pro

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	Specialized FACT 11m, XC Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing
FORCELLA	RockShox Reba RL 29, Motion Control damper, 42mm offset, 15x110mm thru-axle, 100mm of travel
ATTACCO	Specialized XC, 3D-forged alloy, 4-bolt, 6-degree rise
MANUBRIO	Specialized Alloy Minirise, 10mm rise, 750mm, 31.8mm clamp
MANOPOLE	Specialized Trail Grips
FRENO ANT.	SRAM Level TL, hydraulic disc
FRENO POST.	SRAM Level TL, hydraulic disc
CAMBIO POST.	SRAM NX Eagle, 12-speed
COMANDI	SRAM NX Eagle, trigger, 12-speed
CASSETTA	SRAM NX Eagle, 12-speed, 11-50t
CATENA	SRAM NX Eagle, 12-speed
GUARNITURA	Truvativ STYLO, DUB
INGRANAGGI	Alloy, 32T
MOVIM. CENTR.	SRAM DUB, threaded BB
CERCHI	Roval Control Alloy 29", 25mm internal width
MOZZO ANT.	Specialized, sealed cartridge bearings, 15x110mm thru-axle, 24h
MOZZO POST.	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 28h
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry Power Sport, hollow Cr-Mo rails
REGGISELLA	Specialized, alloy, single-bolt, 30.9mm

EPIC HARDTAIL COMP	S	M	L	XL
Stack (mm)	608	608	622	636
Reach (mm)	405	430	455	480
Lunghezza Tubo sterzo (mm)	95	95	110	125
Angolo sterzo (degrees)	68.5	68.5	68.5	68.5
Altezza Mov. Centr. (mm)	309	309	309	309
BB Drop (mm)	63	63	63	63
Trail (mm)	101	101	101	101
Lunghezza intera forcella (mm)	506	506	506	506
Offset forcella / Rake (mm)	42	42	42	42
Avancorsa (mm)	668	693	723	753
Lunghezza Batticateni (mm)	430	430	430	430
Interasse (mm)	1090	1115	1146	1176
Lunghezza Tubo Orizz. virtuale (mm)	579	604	633	662
Altezza standover (mm)	762	792	816	847
Lunghezza piantone (mm)	400	430	470	520
Angolo Sella (degrees)	74	74	74	74

ART. NR.	DESCRIZIONE	COLORE	MISURA
91320-5202	EPIC HT COMP CARBON 29	Carbonio Satinato / Fluo	S
91320-5203			M
91320-5204			L
91320-5205			XL
91320-5002	EPIC HT COMP CARBON 29	Grigio Tortora Lucido / Perlato Blu / Blu Pro	S
91320-5003			M
91320-5004			L
91320-5005			XL

EPIC HARDTAIL

Euro 2.199,00



Nero Satinato / Bianco



Rosso / Bianco Metallizzato

SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

TELAIO	Specialized FACT 11m, XC Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing
FORCELLA	RockShox Judy Gold 29, Motion Control damper, 42mm offset, 15x110mm thru-axle, 100mm of travel
ATTACCO	Specialized XC, 3D-forged alloy, 4-bolt, 6-degree rise
MANUBRIO	Specialized Alloy Minirise, 10mm rise, 750mm, 31.8mm clamp
MANOPOLE	Specialized Trail Grips
FRENO ANT.	Shimano MT-501, hydraulic disc, resin pad
FRENO POST.	Shimano MT-501, hydraulic disc, resin pad
CAMBIO POST.	SRAM NX Eagle, 12-speed
COMANDI	SRAM SX Eagle, trigger, 12-speed
CASSETTA	SRAM PG-1210 Eagle, 11-50t
CATENA	SRAM SX Eagle, 12-speed
GUARNITURA	SRAM X1000 Eagle, DUB, 170/175mm
INGRANAGGI	Steel, 32T
MOVIM. CENTR.	SRAM DUB, threaded BB
CERCHI	Specialized XC 29, 25mm internal width, disc-specific
MOZZO ANT.	Specialized, sealed cartridge bearings, 15x110mm thru-axle, 24h
MOZZO POST.	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 28h
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry Power Sport, hollow Cr-Mo rails
REGGISELLA	Specialized, alloy, single-bolt, 30.9mm

EPIC HARDTAIL	XS	S	M	L	XL
Stack (mm)	594	608	608	622	636
Reach (mm)	385	405	430	455	480
Lunghezza Tubo sterzo (mm)	95	95	95	110	125
Angolo sterzo (degrees)	68.5	68.5	68.5	68.5	68.5
Altezza Mov. Centr. (mm)	309	309	309	309	309
BB Drop (mm)	63	63	63	63	63
Trail (mm)	101	101	101	101	101
Lunghezza intera forcella (mm)	486	506	506	506	506
Offset forcella / Rake (mm)	42	42	42	42	42
Avancorsa (mm)	641	668	693	723	753
Lunghezza Batticateni (mm)	430	430	430	430	430
Interasse (mm)	1062	1090	1115	1146	1176
Lunghezza Tubo Orizz. virtuale (mm)	555	579	604	633	662
Altezza standover (mm)	732	762	792	816	847
Lunghezza piantone (mm)	367	400	430	470	520
Angolo Sella (degrees)	74	74	74	74	74

ART. NR.	DESCRIZIONE	COLORE	MISURA
91320-7101	EPIC HT CARBON 29	Nero Satinato / Bianco	XS
91320-7102			S
91320-7103			M
91320-7104			L
91320-7105			XL
91320-7002	EPIC HT CARBON 29	Rosso / Bianco Metallizzato	S
91320-7003			M
91320-7004			L
91320-7005			XL